




GE  
Lighting



12  
kWh/1000h

A+  
energy class

96  
lumens/watt

## GE Bright Stik™

LED12/STIK/840/220-240V/E27/BX

# 93064025

### Product information

LED Bright Stik™ illuminates spaces with light instantly. Its sleek cylindrical shape fits in place of a traditional incandescent bulb - and some sockets where a traditional bulb or CFL doesn't fit. Replace a 40W, 60W & 100W incandescent with an LED Bright Stik and keep saving for the next 15 years\*. That's a long time you can spend not worrying about light bulbs.

### Application areas

Retail

Hospitality

Home

## Product data

Product Code	93064025
Bulb Shape	T45
Bulb Finish	White
Bulb maximum overall diameter [mm]	45
Nominal Length [mm]	137.5
Net weight per piece [g]	69
RoHS compliant	Yes
Brand	GE BX
Cap/Base	E27

## Performance data

Nominal/ Rated Beam Angle [°]	240
Weighted energy consumption [kWh/1000h]	12
Nominal Initial Lumens per Watt [lm/W]	95.8
Rated efficacy [lm/W]	95.8
Energy efficiency class (EEC)	A+
Rated life L70/B50 [h]	15000
Nominal correlated colour temperature (CCT) [K]	4000
Nominal lumens [lm]	1150
Colour Rendering Index (CRI) [Ra]	80

## Electrical data

Nominal lamp power factor..	>0.5
Operating Temperature (MIN) [°C]	-20°C
Operating Temperature (MAX) [°C]	+40°C
Startup time [sec]	<0.5s
Power Factor	>0.5
Number of switching cycles	50000
Dimming Capability	No
Nominal lamp voltage range [V]	220-240V
Nominal power [W]	12

## Logistic data

DUN Code	10064894573955
EAN Code	0064894573958
Pack Quantity	15
Inner pack type	Box
Outer pack type	Carton
Product status	Available

## Downloads & Links

[Go to the catalog site \(HTTP\)](#)

[Product range datasheet \(PDF\)](#)

[Datasheets \(HTTP\)](#)

[Images \(HTTP\)](#)

[Lighting design tools & calculators \(HTTP\)](#)

[Certificate for the Quality Management System of GE Lighting EMEA \(PDF\)](#)

[Certificate for the Environmental Management System of GE Lighting EMEA \(PDF\)](#)