

## KATRO V2LED

### Downlight fitting



[V] 220-240 AC	[Hz] 50/60	[°] 110	[h] ≥20000	[h] 15000	[°] ≤60 (Machdam)	Ra ≥80
SMD	IP 44/20	[°C] 5÷25	0.5m	[°C] 5÷25	0.5m	CE
	[mm] 0.05	[mm] 0.75				EAC



		[W]		[lm]	[°]	Tc [K]
KATRO V2LED 12W-NW-SN	<b>27214</b>	12	nickel satin	780	110	4000
KATRO V2LED 18W-NW-SN	<b>27215</b>	18	nickel satin	1250	110	4000
KATRO V2LED 24W-NW-SN	<b>27216</b>	24	nickel satin	1700	110	4000
KATRO V2LED 6W-NW-SN	<b>27217</b>	6	nickel satin	300	110	4000
KATRO V2LED 12W-NW-SR	<b>28939</b>	12	silver	660	110	4000
KATRO V2LED 12W-NW-W	<b>28940</b>	12	white	780	110	4000
KATRO V2LED 12W-WW-W	<b>28941</b>	12	white	720	110	3000
KATRO V2LED 18W-NW-SR	<b>28942</b>	18	silver	1080	110	4000
KATRO V2LED 18W-NW-W	<b>28943</b>	18	white	1260	110	4000
KATRO V2LED 18W-WW-W	<b>28944</b>	18	white	1200	110	3000
KATRO V2LED 6W-NW-W	<b>28946</b>	6	white	330	110	4000



- Enclosure material: aluminum alloy
- Lampshade material: plastic

## KATRO V2LED

Downlight fitting



KATRO V2LED 12W-NW-SN



KATRO V2LED 18W-NW-SN



KATRO V2LED 24W-NW-SN



KATRO V2LED 6W-NW-SN



KATRO V2LED 12W-NW-SR



KATRO V2LED 12W-NW-W



KATRO V2LED 18W-NW-SR



KATRO V2LED 18W-NW-W

## KATRO V2LED


### Downlight fitting




KATRO V2LED 18W-WW-W




KATRO V2LED 6W-NW-W




KATRO V2LED 12W



KATRO V2LED 18W



KATRO V2LED 24W



KATRO V2LED 6W