
ITUNGSRAM

Innovation is our heritage EST. 1896







Floodlight LED Flood G1 TU S 30W 840 SY ST BN 93101678

Product information

LED Floodlight is a universal, compact range of floodlights with six lumen output levels from 2.000 to 20.000lm and up to 130 LPW efficiency. The range is suitable for various applications wall mounted around building facades, ideal for the classic floodlighting of buildings as well as lighting gardens, paths near to buildings, garages, entrance ways and drives. Compared to traditional floodlights Tungsram LED Floodlight supplies immediate light without start-up or cooling down times. Thanks to a robust aluminium housing with safety glass cover, the floodlights are ideal for outdoor use.



Product data

Mounting type	Wall mounted
Brand	TUNGSRAM
IP Rating	65
Certifications	CE/EAC
Body colour	Black
Impact resistance	IK07
Weight [kg]	0.97
DIALux description	GE - Floodlight - 3000lm - 30W - 4000K - 80CRI - 93101678[SKU] - Wall mounted
IEC protection classes	Class I
Impact resistance (IK)	IK07
Dimensions	202x203x36mm
Energy efficiency class (EEC)	A+

Performance data

Operating Voltage	220-240V
Ambient Temperature [°C]	-20°C to +40°C
Rated efficacy [lm/W]	100
Total system power	30
Nominal lumens [lm]	3000
Rated lumens [lm]	3000
Rated power [W]	30
Rated life [h]	30000
Nominal correlated colour temperature (CCT) [K]	4000
Colour rendering index (CRI) [Ra]	80+

Optical data



Electrical data

Nominal lamp power factor >0.95


Controllability Not dimmable electronic (Static)


Logistic data


Product status Available

Shipment Standard

Photometric Data







Downloads & Links

Go to the catalog site (HTTP)

Datasheet - TUNGSRAM (PDF)

Datasheet - GE Lighting (PDF)

Installation guide (PDF)

Images (HTTP)

DoC Document (PDF)